This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

De	efects in the images include but are not limited to the items checked:
	☐ BLACK BORDERS
	☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
	☐ FADED TEXT OF DRAWING
	☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
	☐ SKEWED/SLANTED IMAGES
	☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
	☐ GRAY SCALE DOCUMENTS
	☐ LINES OR MARKS ON ORIGINAL DOCUMENT
	☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
	OTHER.

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/736,069	12/13/2000	Doreen Yining Cheng	US 000045	7727
7.	590 09/09/2004		EXAM	INER
Corporate Pat	ent Counsel	PATEL, ASHOKKUMAR B		
U.S. Philips Co 580 White Plair			ART UNIT	PAPER NUMBER
Tarrytown, NY			2154	

DATE MAILED: 09/09/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

RECEIVED

SEP 2 3 2004

Technology Center 2100

			\mathcal{L}
	Application No.	Applicant(s)	V S
Office Action Comments	09/736,069	CHENG, DOREEN	YINING
Office Action Summary	Examiner	Art Unit	
	Ashok B. Patel	2154	
The MAILING DATE of this communication ap Period for Reply	pears on the cover sheet	with the correspondence add	Iress
A SHORTENED STATUTORY PERIOD FOR REPL THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a replif NO period for reply is specified above, the maximum statutory period. - Failure to reply within the set or extended period for reply will, by statut Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	136(a). In no event, however, may oly within the statutory minimum of the will apply and will expire SIX (6) Mode, cause the application to become	a reply be timely filed nirty (30) days will be considered timely. DNTHS from the mailing date of this con ABANDONED (35 U.S.C. § 133).	nmunication.
Status			
1) ☐ Responsive to communication(s) filed on 30 J 2a) ☐ This action is FINAL . 2b) ☐ This 3) ☐ Since this application is in condition for alloware closed in accordance with the practice under the second	s action is non-final. ance except for formal ma	• •	merits is
Disposition of Claims			
4) Claim(s) 1,4,8 and 11-15 is/are pending in the 4a) Of the above claim(s) is/are withdra 5) Claim(s) is/are allowed. 6) Claim(s) 1,4,8 and 11-15 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/o	awn from consideration.		
Application Papers			
9)⊠ The specification is objected to by the Examine			
10) The drawing(s) filed on is/are: a) acc			
Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct	• , ,	· · ·	9 4 49474)
11) The oath or declaration is objected to by the E	· · · · · · · · · · · · · · · · · · ·	- ,	• •
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority document 2. Certified copies of the priority document 3. Copies of the certified copies of the priority document application from the International Bureat * See the attached detailed Office action for a list	its have been received. Its have been received in prity documents have been au (PCT Rule 17.2(a)).	Application No In received in this National S	Stage
Attachment(s)			
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08 Paper No(s)/Mail Date	Paper No	/ Summary (PTO-413) o(s)/Mail Date f Informal Patent Application (PTO- 	152)

DETAILED ACTION

1. Claims 1, 4, 8, and 11-15 are subject to examination.

Response to Arguments

Specification

- Claims 1 and 11 are objected to because of the following informalities:
 Appropriate correction is required.
 - a. Examiner has noticed that claim 11 is shown as being "currently amended" but it is found to be as "original" and not amended.
 - **b.** Claim 1 incorporates the word "proved" which needs to be replaced by "provide" as the applicant has stated that claim 1 has been amended to include the subject matter of dependent claims 2, 3, 6 and 7.
- 3. Applicant's arguments filed June 30, 2004 have been fully considered but they are not persuasive for the following reasons:
 - **a.** Applicant's remarks that claim 13 have been amended to recite the element "selectively translate...without translation." Examiner has noticed that claim 13 does not recite "selective translation."
 - **b.** In response to Applicant's argument that "As noted above, Eytchison discloses a system that translates every message transmitted from one network to the other. Eytchison does not disclose or suggest "to selectively translate a first set of communications between the Web browser and the first network, and to pass a second set of communications between the Web browser and the first network without translation," as is claimed. Saito teaches that when there are IP devices

on the non-IP network, access to the IP devices may be obtained by knowing a global address of the IP devices. However, this is a specific configuration taught by Saito that Saito depends upon to not perform normally required translation from one network to another. This specific teaching is not appropriate when there are only non-IP devices on the non-IP network. Accordingly, one skilled in the art would not look to Saito to teach or suggest selective translation when transferring messages from one network to another as Saito fails to teach selective translation of messages when the non-p network does not include IP devices.", the reference Eytchison teaches a bridge (Fig. 6, element 506) that is configured to facilitate communications between a first network of Non-IP compatible entities (Fig. 6, HAVi Network) and a second network of IPcompatible entities (Fig. 6, VHN network that uses internet protocols, page 4 and 5, [0051]) comprising: a Non-IP (Fig. 6, HAVi Network) to IP interface (Fig. 6, element 600) that is configured to facilitate communications between an application entity on the first network and a Web server on the second network, (Fig., 6, element 616) and, an IP to Non-IP interface (Fig. 6, element 602) that is configured to facilitate communications between a Web browser on the second network and a Non-IP device entity on the first network. (page 6, [0066]) with translation capabilities as Applicant has stated, and the reference Saito teaches the IP devices located in the non-IP network. (Fig. 7, elements 210 and 211). The reference also teaches that these devices can have their own global

IP addresses and as such the routing mechanism in the form of routing table is provided such that the communications to these devices coming from IP network is not translated because it does not need to be translated. (col. 19, lines 6-26). Thereby, the reference teaches to configure the interface to selectively translate a set of communications, for the devices which do not have their own global IP addresses, between the Web server and the first network, and to pass a second set of communications, for the devices which do have their own global IP addresses, between the Web server and the first network without translation. This ability of Saito explicitly suggests to the one having ordinary skill in the art a methodology of "selective translation" for the networks communicating and wherein the networks incorporate the IP as well as non-IP devices.

c. In response to Applicant's arguments that "Furthermore, even if the teachings of Eytchison and Saito can be combined, as suggested by the examiner, the combined device would not include all the elements of the present invention. The device of Eytchison teaches translation of all the communications between networks and includes no discussion or teaching to include mapping or identification of devices that do not require translation or to distinguish IP and non-IP devices. Accordingly, the combined device would not render obvious the present invention because the combined device would not include all the elements of the present invention.", as indicated in the previous office action, the reference Saito

teaches "that these devices can have their own global IP addresses and as such the routing mechanism in the form of routing table (mapping table) is provided such that the communications to these devices coming from IP network is not translated because it does not need to be translated. (col. 19, lines 6-26).

d. Thus, as stated above, based on the teachings of both references as reasoned, they do provide motivation, knowledge that is necessary for one having ordinary skill in the art, and provides reasonable expectations of success for combing them.

Claim Rejections - 35 USC § 103

- 4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 5. Claims 1, 4, 8, 11-15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Eytchison (US Pub. No. US 2001/0047431) in view Saito et al. (hereinafter Saito) (US 6, 523, 696).

Referring to claim 1 and 4,

The reference Eytchison teaches a bridge (Fig. 6, element 506) that is configured to facilitate communications between a first network of Non-IP compatible entities (Fig. 6, HAVi Network) and a second network of IP-compatible entities (Fig. 6,

VHN network that uses internet protocols, page 4 and 5, [0051]) comprising: a Non-IP (Fig. 6, HAVi Network) to IP interface (Fig. 6, element 600) that is configured to facilitate communications between an application entity on the first network and a Web server on the second network, (Fig., 6, element 616). (The reference also teaches this interface contains IP web client which supports TCP/IP and web protocols. (page 6, [0066])(an IP Web client that is operably coupled to the second network). The interface also contains web server that is able to send HTML pages to VHN process, (page 6, [0066]) and interacts with HAVi-VHN DCM as shown in Fig.6, page 6, [0063]) (a Non-IP Web proxy that is operably coupled to the IP Web client and the first network, and is configured to make the IP Web client compliant with middleware that is associated with the Non-IP network; and). (the Non-IP Web proxy is configured to facilitate communications between the web server and a Non-IP service). The reference also teaches the interface containing modified web browser that is able to receive HTML pages and translate then into HAVi messages. (page 6, [0066])(a Non-IP Web proxy client that is operably coupled to the Non-IP Web proxy and the first network, and is configured to allow the application entity to access the Web server.) The reference Eytchison also teaches an IP to Non-IP interface (Fig. 6, element 602) that is configured to facilitate communications between a Web browser on the second network and a Non-IP device entity on the first network. (page 6, [0066]). The reference Eytchison fails to specifically teach the bridge wherein an IP Web client to selectively translate a first set of communications between the Web server and the first network, and to pass a second set of

Application/Control Number: 09/736,069

Art Unit: 2154

communications between the Web server and the first network without translation, an Non-IP Web server to selectively translate a first set of communications between the Web browser and the first network, and to pass a second set of communications between the Web browser and the first network without translation, and a Web service executor that is operably coupled to the Non-IP web server and to the first network, and is configured to provide access to the Non-IP device entity, and a Web page generator that is operably coupled to-the Non-IP Web Server and to the first network, and is configured to generate web pages for presentation to the Web browser; and a translation manager that is operably coupled to the Non-IP Web server, the Web service executor, and the Web page generator, and is configured to provide service-to-user-interface and message-to-methods translation services. The reference Saito teaches the IP devices located in the non-IP network. (Fig. 7, elements 210 and 211). reference also teaches that these devices can have their own global IP addresses and as such the routing mechanism in the form of routing table is provided such that the communications to these devices coming from IP network is not translated because it does not need to be translated. (col. 19, lines 6-26). Thereby, the reference teaches to configure the interface to selectively translate a first set of communications between the Web server (browser) and the first network, and to pass a second set of communications between the Web server (browser) and the first network without translation. The reference Saito teaches the interface (Fig. 44, element 2201) AV connection device 2201 between the first network in a form of the home network 2010 (non-IP network) having the

private IP address space and the second network in a form of Internet 2101 having the global IP address space (IP network). (col. 47, lines 57-63). The reference teaches the elements 2202 (Fig. 44, IP processing unit) and 2205 (Fig. 44, internet I/F) which forms an interface to the Non-IP network (col. 42. lines 39-55). (a Non-IP Web server that is operably coupled to the second network, and is configured to appear as an Internet server to the Web browser:). The reference also teaches the proxy processing unit 2203 in Fig. 2 which detects and collects the services within the home network 2010 as described in col. 42, lines 39-55) (a Web service executor that is operably coupled to the Non-IP Web server and to the first network, and is configured to provide access to the Non-IP device entity;). The reference also teaches home page processing unit 2204 in Fig. 44, a home page processing unit 2204 for creating home pages for the devices/services on the home network 2010 that enables remote control of the devices/services from Internet 2101 side, and delivering the home pages in response to requests. (col. 42, lines 39-55). (a Web page generator that is operably coupled to the Non-IP Web server and to the first network, and is configured to generate web pages for presentation to the Web browser; and). The reference also teaches NAT processing unit translation service between the global IP address (IP network) and the private IP address (non-IP network) (col. 42, lines 56-67 and col. 43, lines 1-12). a translation manager that is operably coupled to the Non-IP Web server, the Web service executor, and the Web page generator, and is configured to provide service-to-user interface and message-tomethods translation services.) Therefore, it would have been obvious to one

Application/Control Number: 09/736,069

Art Unit: 2154

having ordinary skill in the art at the time of invention was made to combine Eytchison with Saito to modify it's HBCM web server (Fig. 6, element 616) such that the IP devices located both in the non-IP network and IP network, and having their global IP addresses get their messages directly from the IP network or non-IP network through routing table as taught by Saito. This allows the IP devices located in the Non-IP and IP networks as shown by Saito to communicate with each other without being interfered by the interface.

Referring to claim 8,

The reference Eytchison teaches a Non-IP network comprising at least one Non-IP-compatible device, (Fig. 6, element 504, 608). The reference Eytchison teaches of the protocol translator 506, (Fig. 6) which is a bridge and can be located on a device physically or logically. (page 5, [0056]) (and a bridge that includes) a Non-IP (Fig. 6, HAVi Network) to IP interface (Fig. 6, element 506, element 600, VBCM) that is configured to facilitate communications between an application entity on the Non-IP network and a Web server on an IP network, (Fig., 6, element 616), and an IP to Non-IP interface (Fig. 6, element 506, element 602, HBCM) that is configured to facilitate communications between a Web browser on the IP network and the at least one Non-IP-compatible device on the Non-IP network (page 6, [0066]). The reference teaches the non-IP to IP interface (Fig. 6, element 600). The reference also teaches this interface contains IP web client which supports TCP/IP and web protocols. (page 6, [0066])(an IP Web client that is operably coupled to the IP network, and is configured to appear as a client to the Web server;) The interface also contains

web server that is able to send HTML pages to VHN process, (page 6, [0066]) and interacts with HAVi-VHN DCM as shown in Fig.6, page 6, [0063]) (a Non-IP Web proxy that is operably coupled to the IP Web client and the Non-IP network, and is configured to make the IP Web client compliant with middleware that is associated with the Non-IP network; and). The reference also teaches the interface containing modified web browser that is able to receive HTML pages and translate then into HAVi messages. (page 6, [0066])(a Non-IP Web proxy client that is operably coupled to the Non-IP Web proxy and the Non-IP network. and is configured to allow the application entity to access the Web server.). The reference fails to specifically teach to selectively translate a first set of communications between the Web server and the Non-IP network, and to pass a second set of communications between the Web server and the Non-IP network without translation. The reference Saito teaches the IP devices located in the non-IP network. (Fig. 7, elements 210 and 211). The reference also teaches that these devices can have their own global IP addresses and as such the routing mechanism in the form of routing table is provided such that the communications to these devices coming from IP network is not translated because it does not need to be translated. (col. 19, lines 6-26). Thereby, the reference teaches to configure the interface to selectively translate a first set of communications between the Web server and the Non-IP network, and to pass a second set of communications between the Web server and the Non-IP network without translation. Therefore, it would have been obvious to one having ordinary skill in the art at the time of invention was made to combine Eytchison with Saito

Application/Control Number: 09/736,069

Art Unit: 2154

to modify it's VBCM web client such that the devices located in the non-IP network and having their global IP addresses get their messages directly from the IP network through routing table as taught by Saito. This allows the IP devices located in the Non-IP network like shown by Saito to communicate with other IP devices without being interfered by the interface.

Referring to claim 11,

Keeping in mind the teachings of Keeping in mind the teachings of Evtchison as stated above for the Non-IP to IP interface, although the reference teaches the IP to Non-IP interface (Fig.6, element 602, HBCM) and although the reference teaches the interface (the bridge), the protocol translator 506, (Fig. 6) which is a bridge and can be located on a device physically or logically. (page 5, [0056]), it does not explicitly teach the claimed elements of claims 5 and 11. The reference Saito teaches such interface elements. The reference Saito teaches the interface (Fig. 44, element 2201) AV connection device 2201 between the first network in a form of the home network 2010 (non-IP network) having the private IP address space and the second network in a form of Internet 2101 having the global IP address space (IP network). (col. 47, lines 57-63). The reference teaches the elements 2202 (Fig. 44, IP processing unit) and 2205 (Fig. 44, internet I/F) which forms an interface to the Non-IP network (col. 42, lines 39-55). (a Non-IP Web server that is operably coupled to the second network, and is configured to appear as an Internet server to the Web browser;). The reference also teaches the proxy processing unit 2203 in Fig. 2 which detects and collects the services within the home network 2010 as described in col. 42, lines 39-55) (a Web

service executor that is operably coupled to the Non-IP Web server and to the first network, and is configured to provide access to the Non-IP device entity;). The reference also teaches home page processing unit 2204 in Fig. 44, a home page processing unit 2204 for creating home pages for the devices/services on the home network 2010 that enables remote control of the devices/services from Internet 2101 side, and delivering the home pages in response to requests. (col. 42, lines 39-55). (a Web page generator that is operably coupled to the Non-IP Web server and to the first network, and is configured to generate web pages for presentation to the Web browser; and). The reference also teaches NAT processing unit translation service between the global IP address (IP network) and the private IP address (non-IP network) (col. 42, lines 56-67 and col. 43, lines 1-12), a translation manager that is operably coupled to the Non-IP Web server, the Web service executor, and the Web page generator, and is configured to provide service-to-user interface and message-to-methods translation services.) Therefore, it would have been obvious to one having ordinary skill in the art at the time of invention was made to combine Eytchison's HBCM's functionality with Saito's functional modules as shown in Fig. 44 such that it is equally applicable to any of the following combinations for the first and second networks, (1) a combination of global IP address and private IP address, (2) a combination of IPv4 address and IPv6 address and (3) a combination of IPv6 address and link local IPv6address as taught by Saito.

Referring to claims 13 and 14,

Keeping in mind the teachings of Eytchison as stated above, the reference teaches the method of claims 13 and 14. (Page 5, [0057-[0059] and page 6, [0070]-[0079]), however, the reference fails to teach wherein a first set of communications are translated and passed between the browser and the non-IP network, and a second set of communications are passed between the browser and the Non-IP network without translation. The reference Saito teaches the IP devices located in the non-IP network as well as IP network. (Fig. 7, elements 206, 207, 210 and 211). The reference also teaches that these devices can have their own global IP addresses and as such the routing mechanism in the form of routing table is provided such that the communications to these devices coming from IP network is not translated because it does not need to be translated. (col. 19, lines 6-26). Thereby, the reference teaches to configure the interface to selectively translate a first set of communications between the Web server and the first network, and to pass a second set of communications between the Web server and the first network without translation. Therefore, it would have been obvious to one having ordinary skill in the art at the time of invention was made to combine Eytchison with Saito to modify it's HBCM web server (Fig. 6, element 616) such that the IP devices located both in the non-IP network and IP network, and having their global IP addresses get their messages directly from the IP network or non-IP network through routing table as taught by Saito. This allows the IP devices located in the Non-IP and IP networks as shown by Saito to communicate with each other without being interfered by the interface.

Referring to claim 15,

Keeping in mind the teachings of Eytchison as stated above, the reference also teaches the method of claim 15. (Page 7, [0080]-[0083] and page 8, [0084]).

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Ashok B. Patel whose telephone number is (703) 305-2655. The examiner can normally be reached on 8:00am-5:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, John A Follansbee can be reached on (703) 305-8498. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Abp